

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 1 of 6

| Evaluation | Citation / Method | No. of Samples | Criteria | Notes | Result | Rating | |
|------------------------------------|-----------------------------------|-------------------|--|-------|--------|--------|--|
| SCOPE: This protocol is applic | | | | | | | |
| SUPPLEMENTARY P | ROTOCOL | | | | | | |
| Note: Additional cost, s | sample size & TAT may | be required if te | sting to 1 or more supplemental protocols is necessary. | | | | |
| Diagon refer to the hele | vu votovonood oumnlous | antal protocol(a) | for additional information | | | | |
| Please relei to the beit | ow referenced suppleme | ental protocol(s) | for additional information. | | | | |
| A California | DILL-AN-PTCL- | 1 | The sample should be reviewed against the requirements of California | | | | |
| R Proposition 65 | 06572-USA | • | Proposition 65. | | | | |
| LABELING | | | · | | | | |
| US Packaging | F.P. and L. Act | 1 | Packaging shall be labelled with the following, | | | | |
| M labeling | (16 CFR 500) OR | | Product Identification | | | | |
| R | NIST Uniform | | Net quantity of contents shall be expressed in terms of weight or mass, | | | | |
| | Laws and | | measure, numerical count, or combination so as to give accurate information to | | | | |
| | Regulations Handbook 130 | | facilitate consumer comparison (U.S. and metric units) | | | | |
| | Handbook 130 | | Manufacturer, packer, or distributor's name & address (City, State & Zip Code) | | | | |
| Country of origin | 19 CFR 134 | 1 | Shall indicate country of origin legibly, permanently, and in comparable size and | | | | |
| M marking | | | close proximity to any mention of country other than country in which the article | | | | |
| R | | | was manufactured or produced. Must be visible at point of purchase. | | | | |
| Use labeling | CPSD-GB-01057- | 1 | Use/care instructions shall be clear, concise and understandable, provide step- | | | | |
| | MTHD | | by-step method of use and be provided in language appropriate to destination | | | | |
| 1 -1 -1 | 40.050.04 | | countries. Provide a copy of the instructions in the report. | | | | |
| Labeling review: R leather | 16 CFR 24 | 1 | Must conform to guidelines for leather content / general fiber content labeling | | | | |
| R leather | | | If all or part of a product is made of non-leather material that appears to be | | | | |
| | | | leather, the non-leather material must be disclosed on the retail packaging. The | | | | |
| | | | disclosure must be of such conspicuousness and clarity as to be noted by | | | | |
| | | | consumers casually inspecting the product. The disclosure must be in close | | | | |
| | | | proximity to the product identification. | | | | |
| | | | | | | | |
| | | | NOTE: A material that contains ground, pulverized, shredded, reconstituted or | | | | |
| | | | bonded leather cannot be represented as being wholly leather. Adequate | | | | |
| ANIALVEIGAL | | | disclosure of these leather types must be present. | | | | |
| ANALYTICAL | L ODGO OU E4600 | | All and the surface of the surface o | | | | |
| A Total lead in surface coating | CPSC-CH-E1003- 09.1 / CPSD-AN- | - | All accessible surface coatings in the as received state on items outside of the scope of 16 CFR 1303 shall not contain lead or lead components in which the | | | | |
| surface coating | 03.17 CP3D-AN- | | Scope of 16 CFR 1303 Shall not contain lead of lead components in which the | | | | |



BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 2 of 6

| Evaluation | Citation / Method | No. of Samples | Criteria Criteria | Notes | Result | Rating |
|-----------------------------|------------------------|-------------------|--|-------|--------|----------|
| | 00001-MTHD | | lead content is in excess of 0.009% (90 ppm) of the weight of the total content. | | | |
| | | | Report actual results or include data table within report. | | | |
| | | | Component testing is allowed. | | | |
| | | | Compositing up to 3 colors is allowed. | | | |
| | | | Client requirement | | | |
| PHYSICAL CHARACT | | ' | | • | • | |
| Dimensions - height | CPSD-GB-01056- MTHD | 1 | Report overall height. Shall meet label claims. | | | |
| Dimensions - | CPSD-GB-01056- | 1 | Report overall width; shall meet label claims | | | |
| width Dimensions - | MTHD CPSD-GB-01056- | 1 | Depart averall depths shall most label slaims | | - | \vdash |
| depth | MTHD | ı | Report overall depth; shall meet label claims. | | | |
| Dimensions | CPSD-GB-01056- MTHD | 1 | [Handle drop] | | | |
| | | | Report overall dimensions; shall meet label claims. | | | |
| Dimensions | CPSD-GB-01056- MTHD | 1 | [Circumference - shoulder strap drop] | | | |
| | WITTE | | Report maximum and minimum;shall meet label claims. | | | |
| Dimensions - thickness | CPSD-GB-01056- MTHD | 1 | [Material thickness] | | | |
| | 2 | | Report overall thickness; shall meet label claims (If applicable) (-0% / +5%). | | | |
| Weight | Weight measurements | 1 | Report overall weight; shall meet label claims. (if applicable) (-5% / +5%). | | | |
| Parts inventory | CPSD-GB-01057- MTHD | 1 | Shall meet label claims.All listed hardware must be provided. | | | |
| Number of main compartments | CPSD-GB-01057- MTHD | All | Shall be as claimed. | | | |
| Number of | CPSD-GB-01057- | All | Shall be as claimed. | | | |
| internal pouches | MTHD | | | | | |
| or pockets or | | | | | | |
| openings | ODOD OD 04057 | A II | Ohall ha as alsimod | | - | igwdown |
| Number of | CPSD-GB-01057- | All | Shall be as claimed. | L | | |



BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 3 of 6

| Evaluation | Citation / Method | No. of Samples | Criteria | Notes | Result | Rating |
|---|------------------------------|-------------------|--|-------|--------|--------|
| external pouches or pockets or openings | MTHD | | | | | |
| Other features | CPSD-GB-01057- MTHD | All | Shall be as claimed. | | | |
| Fabric weight | ASTM D3776-20 | 1 | Shall be as claimed (± 5%) | | | |
| | | | For claimed weight submitted in range, $\pm5\%$ applicable on the upper and lower limit of submitted the range. | | | |
| Fabric count of woven fabric | ASTM D3775- 17(R2023) | 1 | Shall be as claimed (± 3.0%). | | | |
| Yarn construction | ASTM D1244- 98(R2020) | 1 | ± 3.0% as claimed | | | |
| Width of textile fabric | ASTM D3774- 18(R2024) | 1 | [Cuttable width] | | | |
| | | | Report as data | | | |
| WORKMANSHIP | | | | | | |
| Hazardous sharp point and sharp edge | 16 CFR 1500.48 & 49 (Mod) | All | Shall have no sharp points / edges, other than those required for function. Modification: Expanded scope to other products. | | | |
| Defects and workmanship | CPSD-GB-01057- MTHD | All | Shall have no discernible surface degradation, including crazing, shivering, denting, bubbles, cracks, stains, deformations, chips, fractures, heavy lines, waves, shear marks, scratches, scuff marks, indentations, or blisters. Shall have no components missing, malformed, and/or fractured. | | | |
| Fabric defects | ASTM D3990-12 (R2020) | 1 | No critical defects. | | | |
| PERFORMANCE | | | | | | |
| Actual use - functionality | CPSD-GB-01058- MTHD | All | Shall function as intended as received. Report details of evaluation (features tested / methods used / materials used / etc.) Report any features not evaluated. | | | |
| Seam strength | ASTM D1683-22 Modified | 2 | Side seam: 15 lb minimum. Bottom seam: 15 lb minimum. Zipper seam: 15 lb minimum. Reinforced stress points: 15 lb minimum. Modification: Expanded the scope to other than apparel. | | | |



BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 4 of 6

| Evaluation | Citation / Method | No. of Samples | Criteria | Notes | Result | Rating |
|--|---------------------------|-------------------|--|-------|--------|--------|
| Handle strength @ 45 degree | ASTM D1683-22 Modified | 2 | 15 lb minimum. Modification: Expanded scope to other products. | | | |
| Handle strength | ASTM D1683-22 Modified | 2 | 15 lb minimum. Modification: Expanded scope to other products. | | | |
| Breaking strength of textile fabrics: grab test | ASTM D5034-21 | 2 | Shell: minimum 20 lbf Lining: minimum 10 lbf Note: Pass / fail base on result of overall fabric break. | | | |
| Holding strength of snap fasteners | ASTM D7142-05 (R2021) | 2 | 17 lb for 10 seconds | | | |
| Resistance to snapping and unsnapping of snap fasteners | CPSD-SL-31045- MTHD | 2 | Minimum 2 lb Maximum 8 lb | | | |
| Button/small parts attachment strength | CPSD-SL-31023- MTHD | 2 | 17 lb minimum for 10 seconds. | | | |
| Button impact resistance | CPSD-SL-31001- MTHD | 2 | No fractures of button. | | | |
| Operability of zippers | ASTM D2062-03 R2021 | 1 | Maximum 10 lb. | | | |
| Strength tests for zippers | ASTM D2061-07 (R2021) | 1 | Cross widthwise strength: 50 lb. minimum. Scoop pull: 10 lb. minimum. Top stop: 20 lb. minimum. Bottom stop: 20 lb. minimum. Slider torque: 2 lb-in minimum. Slider pull: 5 lb. minimum. | | | |
| Abrasion resistance of fabric - Inflated diaphragm apparatus | ASTM D3886-22 | 1 | [Edge] No removal of upper surface after 300 cycles | | | |
| Flexing test | CPSD-SL-81002- | 1 | No cracking after 10,000 cycles | | | |



BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 5 of 6

| Evaluation | Citation / Method | No. of Samples | Criteria | Notes | Result | Rating |
|------------|-------------------|-------------------|----------|-------|--------|--------|
| | MTHD | | | | | |

| No. Of Samples Required for Complete Testing | 3 | |
|--|---|-------------------------------|
| No. Of (Fully Packed) Cartons For Transit Testing: | 1 | (Only upon Dillard's request) |
| No. Of Working Days For Complete Testing: | 7 | |

| Client Approval: | Olivia fu |
|--------------------------|-------------|
| | 03/Jul/2025 |
| Creation Date: | 16/Oct/2014 |
| Last Revision Date: | 25/Apr/2025 |
| Pricing Review Date | |
| Technical Review Date: | 13/Feb/2015 |
| Dillard's Approval Date: | 8/1/25 |

Key A Additional Charge For This Test

Μ Mandatory R Regulatory

Result Key

C Claimed R Recorded M Meets

NM Does Not Meet NA Not Applicable Not Tested NT

Rating Key PASS

Pass **FAIL** Fail

NR Not Requested



BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 6 of 6