




BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: Page 1 of 7

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
<b>SCOPE:</b> This protocol is applicable for testing of handbag for children.						
<b>SUPPLEMENTARY PROTOCOL</b> Note: Additional cost, sample size and TAT may be required if testing to 1 or more supplemental protocol is necessary. Please refer to the below referenced supplemental protocol(s) for additional information.						
A R	California Proposition 65	DILL-AN-PTCL- 06572-USA	-	The sample should be reviewed against the requirements of California Proposition 65.		
<b>LABELING</b>						
M R	US Packaging labeling	F.P. and L. Act (16 CFR 500) OR NIST Uniform Laws and Regulations Handbook 130	1	Packaging shall be labelled with the following, Product Identification Net quantity of contents shall be expressed in terms of weight or mass, measure, numerical count, or combination so as to give accurate information to facilitate consumer comparison (U.S. and metric units) Manufacturer, packer, or distributor's name & address (City, State & Zip Code)		
M R	Labeling review: country of origin	16 CFR 300/303, 19 CFR 134.11	1	Shall indicate country of origin legibly, permanently, and in comparable size and close proximity to any mention of country other than country in which the article was manufactured or produced. Must be visible at point of purchase.		
	Use labeling	CPSD-GB-01057- MTHD	1	Use/care instructions shall be clear, concise and understandable, provide step- by-step method of use and be provided in language appropriate to destination countries. Provide a copy of the instructions in the report.		
	Labeling review: leather	16 CFR 24	All	[Leather labeling]  Must comply with FTC leather labeling guidelines.		
	Claim verification - level 1	CPSD-GB-08612- MTHD	All	Must comply to claims.		
	Producer's markings	ASTM F963-17 Sec. 7 (Mod)	All	[Only if applicable]  Report actual. Shall comply with requirement.		
	Small parts warning	ASTM F963-17 Sec. 4.6-5.11.2 (Mod)	1	[Only if applicable]   <b>WARNING</b>		



BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: Page 2 of 7

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
			CHOKING HAZARD - Small parts. Not for children under 3 yrs.			
<b>ANALYTICAL</b>						
A Total lead in surface coating	CPSC-CH-E1003-09.1 / CPSD-AN-00001-MTHD	-	All accessible surface coatings in the as received state on items outside of the scope of 16 CFR 1303 shall not contain lead or lead components in which the lead content is in excess of 0.009% (90 ppm) of the weight of the total content.  Report actual results or include data table within report. Component testing is allowed. Compositing up to 3 colors is allowed.  Client requirement			
<b>PHYSICAL MECHANICAL AND ELECTRICAL HAZARD</b>						
R Sharp point and sharp edge	16 CFR 1500.48 & 49	All	Shall have no sharp points/edges, other than those required for function.			
R Use and abuse (small parts, sharp edges, points)	16 CFR 1500.48 & 49 / ASTM F963-17 Sec. 4.7 & 4.9 (Mod)	1	No hazards.			
Projections	ASTM F963-17 Sec. 4.8 (Mod)	1	Shall be free from projections.			
Plastic film	ASTM F963-17 Sec. 4.12 (Mod)	1	[Packaging - film]  Shall not be less than 0.0317 mm.			
Torque test for removal of components	ASTM F963-17 Sec. 8.8 (Mod)	1	[As per table 5]  Shall meet all requirement, no hazards.			
Tension test for removal of components	ASTM F963-17 Sec. 8.9 (Mod)	1	[As per table 5]  Shall meet all requirement, no hazards.			
Drop test	ASTM F963-17 Sec. 8.7.1 (Mod)	1	[As Per Table 5]			



BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: Page 3 of 7

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
			Shall meet all requirements, No hazards			
Compression test	ASTM F963-17 Sec. 8.10 (Mod)	1	[As Per Table 5]  Shall meet all requirements, No hazards			
<b>FLAMMABILITY</b>						
Solids - R Flammability	16 CFR 1500.3(c)(6)(vi) / 16 CFR 1500.44	1	Shall not exceed the maximum allowable limit of no greater than 0.1 inches per second.			
<b>PHYSICAL CHARACTERISTICS</b>						
Dimensions	CPSD-GB-01056- MTHD	1	Report overall dimensions; shall meet label claims (If applicable) (-0% / +5%).			
Dimensions - depth	CPSD-GB-01056- MTHD	1	Report overall depth; shall meet label claims.			
Dimensions	CPSD-GB-01056- MTHD	1	[Handle drop]  Report overall dimensions; shall meet label claims.			
Dimensions	CPSD-GB-01056- MTHD	1	[Shoulder strap drop circumference]  Report maximum and minimum dimensions; shall meet label claims.			
Other features	CPSD-GB-01057- MTHD	All	Shall be as claimed.			
Fabric weight	ASTM D3776-20	1	Shall be as claimed (± 5%)			
Dimensions - thickness	CPSD-GB-01056- MTHD	1	[Material qualities]  Report overall thickness; shall meet label claims. (If applicable) (-0% / +5%).			
Number of main compartments	CPSD-GB-01057- MTHD	All	Shall be as claimed.			
Number of internal pouches or pockets or openings	CPSD-GB-01057- MTHD	All	Shall be as claimed.			
Number of external pouches	CPSD-GB-01057- MTHD	All	Shall be as claimed.			



**BUREAU  
VERITAS**

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: **Page 4 of 7**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
or pockets or openings						
Yarn construction	ASTM D1244-98(R2020)	1	± 3.0% as claimed			
Fabric count of woven fabric	ASTM D3775-17e1		Shall be as claimed (± 3.0%).			
<b>WORKMANSHIP</b>						
Fabric defects	ASTM D3990-12 (R2020)	1	No critical / major defects.			
Defects and workmanship	CPSD-GB-01057-MTHD	All	Shall have no discernible surface degradation, including crazing, shivering, denting, bubbles, cracks, stains, deformations, chips, fractures, heavy lines, waves, shear marks, scratches, scuff marks, indentations, or blisters. Shall have no components missing, malformed, and/or fractured.			
<b>PERFORMANCE</b>						
Actual use - functionality	CPSD-GB-01058-MTHD	All	Shall function as intended. Report details of evaluation (materials used / features tested / consumables / method / etc.)			
Breaking strength of textile fabrics: grab test	ASTM D5034-21	2	Shell: minimum 25 lbf Lining: minimum 20 lbf  Note: Pass / fail base on result of overall fabric break.			
Tearing strength: Elmendorf apparatus	ASTM D1424-21	2	Shell: 2.0 lb minimum. Note: "cross tear should be data/numbers"			
Tearing strength: Elmendorf apparatus	ASTM D1424-21	2	Lining: 1.5 lb minimum. Note: "cross tear should be data/numbers"			
Seam strength	ASTM D1683-22 Modified	2	Side seam: 25 lb minimum. Zipper seam: 25 lb minimum. Bottom seam: 25 lb minimum. Lining woven: 20 lb minimum. Vinyl woven: 10 lb minimum.  Modification: Expanded the scope to other than apparel.			



**BUREAU  
VERITAS**

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: **Page 5 of 7**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
Handle strength @ 45 degree	ASTM D1683-22 Modified	2	Clutch: 10 lb minimum. Large: 20 lb minimum. Medium: 15 lb minimum. Mini: 5.0 lb minimum.  Modification = Expanded scope to other products.			
Operability of zippers	ASTM D2062-03 R2021	1	Open and close: 2.0 lb maximum.			
Strength tests for zippers	ASTM D2061-07 (R2021)	1	Cross widthwise strength: 15 lb minimum. Scoop pull: 10 lb minimum. Top stop: 10 lb minimum. Bottom stop: 10 lb minimum. Slider pull: 5 lb minimum. Slider torque: 2 lb minimum.			
Abrasion resistance of fabric: rotary platform abrader method	ASTM D3884-22	1	Abradent: CS17, Head weight, 1000g, 500 cycles  Req.: Loss in breaking: 10% of original break load .			
A Moisture content	CPSD-HL-01063-MTHD	1	[Wood components]  Less than 12%.			
A Drop test	CPSD-HL-01059-MTHD (Mod)	1	[Wood components]  Modification = One 12 in. drop - remain intact.			
Effects of extreme temperature change	CPSD-HL-01012-MTHD	1	Shall withstand for 24 hours at 32 °F and then 24 hours at 120 °F with no structural failure or visual change.  Modification: Exposure time changed from 4 hours to 24 hours.			
Water repellency: spray test	AATCC 22-17	2	[If claimed]  Minimum 90 ISO rating.			



BV Lab Number:  
 Technician Name:  
 Test Date:  
 Reviewed By/Date: **Page 6 of 7**

**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
Resistance to corrosion	ASTM B117-19 modified	1	<p>[Applicable to samples or sample components constructed of metal or samples with metallic coatings that can be exposed to the environment]</p> <p>Shall withstand 24 hours in 1% salt spray (fog) with no noticeable oxidation / corrosion / visual changes.</p> <p>Modification: 1% salt spray (fog).</p>			
<b>COLORFASTNESS</b>						
Colorfastness to crocking	AATCC 8-16	1	<p>[Face / Back / Edge]</p> <p>General:            Dry: Grade 4.0 minimum            Wet: Grade 3.0 minimum</p> <p>Dark Color:            Dry: Grade 3.0 minimum            Wet: Grade 2.0 minimum</p>			
Colorfastness to rotary crocking	AATCC 116-18	1	<p>[Face / Back / Edge]</p> <p>General:            Dry: Grade 4.0 minimum            Wet: Grade 3.0 minimum</p> <p>Dark Color:            Dry: Grade 3.0 minimum            Wet: Grade 2.0 minimum</p>			

No. Of Samples Required for Complete Testing	2	
No. Of (Fully Packed) Cartons For Transit Testing:	1	Only Upon Dillard's Request

Client Approval:	Lucy Feng
	09/Jun/2023
Creation Date:	15/Apr/2003



**DILLARD'S INC TEST PROTOCOL FOR**  
**DILL-02062-USA- (V34)**  
**HANDBAG (CHILDREN)**

BV Lab Number:  
 Technician  
 Name:  
 Test Date:  
 Reviewed  
 By/Date: **Page 7 of 7**

No. Of Working Days For Complete Testing:	5	
---	---	--

Last Revision Date:	07/Jun/2023
Pricing Review Date	
Technical Review Date:	

**Key**

A Additional Charge For This Test  
 M Mandatory  
 R Regulatory

**Result Key**

C Claimed  
 R Recorded  
 M Meets  
 NM Does Not Meet  
 NA Not Applicable  
 NT Not Tested

**Rating Key**

PASS Pass  
 FAIL Fail  
 NR Not Requested