

DILLARD'S INC TEST PROTOCOL FOR DILL-02063-USA- (V29) SMALL NON-LEATHER GOODS (POUCHES, HOLDERS, ETC.)

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 1 of 5

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
SCOPE:	•					
This protocol is applic	cable for testing of smal	I non-leather go	ods (pouches,holders,etc).			
SUPPLEMENTARY PI						
Note: Additional cost, s	sample size & TAT may	be required if to	esting to 1 or more supplemental protocols is necessary.			
		ental protocol(s)	for additional information.			
A California	DILL-AN-PTCL-	-	The sample should be reviewed against the requirements of California			
R Proposition 65	06572-USA		Proposition 65.			
LABELING						
US Packaging	F.P. and L. Act	1	Packaging shall be labelled with the following,			
M labeling	(16 CFR 500) OR		Product Identification			
R	NIST Uniform		Net quantity of contents shall be expressed in terms of weight or mass,			
	Laws and		measure, numerical count, or combination so as to give accurate information to			
	Regulations		facilitate consumer comparison (U.S. and metric units)			
	Handbook 130		Manufacturer, packer, or distributor's name & address (City, State & Zip Code)			
Country of origin	19 CFR 134	1	Shall indicate country of origin legibly, permanently, and in comparable size and			
M marking			close proximity to any mention of country other than country in which the article			
R			was manufactured or produced. Must be visible at point of purchase.			
Use labeling	CPSD-GB-01057-	1	Use/care instructions shall be clear, concise and understandable, provide step-			
	MTHD		by-step method of use and be provided in language appropriate to destination			
			countries. Provide a copy of the instructions in the report.			
ANALYTICAL						
A Total lead in	CPSC-CH-E1003-	-	All accessible surface coatings in the as received state on items outside of the			
surface coating	09.1 / CPSD-AN-		scope of 16 CFR 1303 shall not contain lead or lead components in which the			
	00001-MTHD		lead content is in excess of 0.009% (90 ppm) of the weight of the total content.			
			Report actual results or include data table within report.			
			Component testing is allowed.			
			Compositing up to 3 colors is allowed.			
			Compositing up to 3 colors is allowed.			
			Client requirement			
PHYSICAL CHARACT	ERISTICS				<u> </u>	
Dimensions	CPSD-GB-01056-	1	Report overall dimensions; shall meet label claims.			
	MTHD		· · · · · · · · · · · · · · · · · · ·			
Dimensions -	CPSD-GB-01056-	1	Report overall thickness. Shall meet label claims.			
thickness	MTHD		·			1



<u>DILLARD'S INC TEST PROTOCOL FOR</u> <u>DILL-02063-USA- (V29)</u> <u>SMALL NON-LEATHER GOODS (POUCHES, HOLDERS, ETC.)</u>

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 2 of 5

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
Weight	CPSD-GB-01056- MTHD	1	Report overall weight; shall meet label claims.			
Capacity - volumetric	CPSD-HL-06000- MTHD	1	Report overall capacity; shall meet label claims.			
Parts inventory	CPSD-GB-01057- MTHD	1	Shall meet label claims.All listed hardware must be provided.			
Features	CPSD-GB-01057- MTHD	All	Shall be as claimed.			
Material type	CPSD-GB-01057- MTHD	1	Shall be as claimed.			
WORKMANSHIP						
Sharp point and sharp edge	16 CFR 1500.48 & 49 (Mod)	All	Shall have no sharp points / edges, other than those required for function. Modification: Expanded scope to other products.			
Defects and workmanship	CPSD-GB-01057- MTHD	All	Shall have no discernible surface degradation, including crazing, shivering, denting, bubbles, cracks, stains, deformations, chips, fractures, heavy lines, waves, shear marks, scratches, scuff marks, indentations, or blisters. Shall have no components missing, malformed, and/or fractured.			
Material quality	CPSD-GB-01057- MTHD	All	No major defects.			
PERFORMANCE						
Actual use - functionality	CPSD-GB-01058- MTHD	All	Shall function as intended as received. Report details of evaluation (features tested / methods used / materials used / etc.) Report any features not evaluated.			
Attachment strength	16 CFR 1500.51- 53 (Mod) / ASTM F963-17 Section 8.8 & 8.9 (Mod)	1	[Additional tests for child and baby leather accessories] 15 lb for 10 seconds. Modification: Expanded the scope to other than apparel.			
Breaking strength of textile fabrics: grab test	ASTM D5034-21		Minimum 25 lbf Note: Pass / fail base on result of overall fabric break.			
Seam strength	ASTM D1683-22 Modified	2	Bottom / side seam: 25 lb. minimum. Lining seams - woven: 7 lb. minimum. Lining seams - vinyl: 10 lb. minimum.			



DILLARD'S INC TEST PROTOCOL FOR DILL-02063-USA- (V29) SMALL NON-LEATHER GOODS (POUCHES, HOLDERS, ETC.)

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 3 of 5

Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
			Zipper seam: 25 lb. minimum. Modification: Expanded the scope to other than apparel.			
Handle strength @ 45 degree	ASTM D1683-22 Modified	2	Handles or shoulder straps: 25 lb minimum. Modification: Expanded scope to other products			
Operability of zippers	ASTM D2062-03 R2021	1	[Open and close]			
Strength tests for zippers	ASTM D2061-07 (R2021)	2	Cross widthwise strength: 50 lb. minimum. Scoop pull: 10 lb. minimum. Top stop: 20 lb. minimum. Bottom stop: 20 lb. minimum. Slider torque: 2 lb-in minimum. Slider pull: 5 lb. minimum.			
Holding strength of snap fasteners	ASTM D7142-05 (R2021)	All	15 lb per 10 seconds			
Resistance to snapping and unsnapping of snap fasteners	CPSD-SL-31045- MTHD	1	Minimum 2 lb Maximum 8 lb			
Button/small parts attachment strength	CPSD-SL-31023- MTHD	1	15 lb for 10 seconds.			
Button impact resistance	CPSD-SL-31001- MTHD	1	No fractures of button.			
Abrasion resistance of fabric - Inflated diaphragm apparatus	ASTM D3886-22	1	No removal of upper surface after 300 cycles			
Resistance to flexing - vinyl	SATRA PM 55 (Mod)	1	Modification: No cracking after 10,000 cycles.			
Resistance to	ASTM B117-19	1	[Applicable to samples or sample components constructed of metal or samples			



<u>DILLARD'S INC TEST PROTOCOL FOR</u> <u>DILL-02063-USA- (V29)</u> <u>SMALL NON-LEATHER GOODS (POUCHES, HOLDERS, ETC.)</u>

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 4 of 5

	Evaluation	Citation / Method	No. of Samples	Criteria	Notes	Result	Rating
	corrosion	modified		with metallic coatings that can be exposed to the environment] Shall withstand 24 hours in 1% salt spray (fog) with no noticeable oxidation / corrosion / visual changes. Modification: 1% salt spray (fog).			
СО	LORFASTNESS					•	
Α	Colourfastness to artificial saliva	DIN 53160- 1:2010-10	1	[Additional test for child and baby leather accessories] Grade 4.0 minimum			
	Colorfastness to crocking	AATCC 8-16	1	[Face/Back/Edge] Dry: Grade 3.0 minimum			
				Wet: Grade 2.0 minimum			
	Colorfastness to rotary crocking	AATCC 116-18	1	[Face / Back / Edge] Dry: Grade 3.0 minimum. Wet: Grade 2.0 minimum.			
	Colorfastness to light	AATCC 16.3-20	1	[Option 3] [Neon and bright colors only] Grade 4.0 minimum at 10 AFU			

No. Of Samples Required for Complete Testing	3	
No. Of (Fully Packed) Cartons For Transit Testing:	1	(Only Upon Dillard's Request)
No. Of Working Days For Complete Testing:	7	

Client Approval:	Lucy Feng
	24/Aug/2022
Creation Date:	06/Jan/2009
Last Revision Date:	
Pricing Review Date	



DILLARD'S INC TEST PROTOCOL FOR DILL-02063-USA- (V29) SMALL NON-LEATHER GOODS (POUCHES, HOLDERS, ETC.)

BV Lab Number: Technician Name: Test Date: Reviewed

By/Date: Page 5 of 5

Technical Review Date:	13/Feb/2015

Additional Charge For This Test

Key A M Mandatory Regulatory R

Result Key

Claimed Recorded R Μ Meets

NM Does Not Meet Not Applicable Not Tested NA NT

Rating Key PASS

Pass FAIL Fail

NR Not Requested